EX-PRO HANDHELD PHONE

NSR Fire-fighter's portable radiotelephone:

- Meet IMO MSC.338 (91) and IMO MSC.149 (77) regulation
- Designed for onboard fire-fighter's communication
- Ex-proof certificated
- Type approval with CCS



According to IMO MSC.338 (91) & SOLAS Chapter II-2, regulation 10.10.4:

Fire-fighter's communication

A minimum of TWO two-way portable radiotelephone apparatus for each fire party for fire-fighter's communication shall be carried on board. Those two-way portable radiotelephone apparatus shall be of an explosion-proof type or intrinsically safe.









SPECIFICATIONS

• FREQUENCY & CHANNEL

- Frequency Range: $156.300\!\sim\!156.875~\text{MHz}$

- Channel Space: 25 kHz

- Usable Channels: 19 channels (default)

• TECHNICAL FEATURE

- Output Power: High 3.0 W / Low 0.5 W

- Communication Methods: Simplex Within 5 sec - Warming Up Time: - Squelch Control: - Dual Watch: - Key Locking:

- Battery Save Mode: - Beep Establishment: - Location Indication:

- Operating Temperature: -20°C~+60°C


- Size: 256 (H) \times 56 (W) \times 46.2 (D) mm - Weight: 280 g (Transceiver + Battery) - IP Grade:

IP67 (Transceiver / Antenna / Battery)

IP22 (Charger / Adaptor)

- Ex Code: Exib IIB T4 Gb - Battery Capacity: 2200 mAh - Battery Voltage: DC 7.2 V

SIZE DIMENSION



EQUIPMENT LIST

STANDARD

- Transceiver & Antenna 1 set - Rechargeable Battery Pack 1 pc - Battery Charger 1 pc - AC/DC Adaptor 1 pc - Belt Clip 1 pc - Wrist Rope 1 pc

OPTIONS

- External PTT & Skull Mic/Headset 1 set





Rechargeable **Battery Pack**

Belt Clip





Battery Charger









